

Safety Data Sheet

Megapoxy

Hazardous Chemical, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **Megapoxy HICB - Part A**

Recommended use: Liquid epoxy grout used for grouting machinery, backing crusher parts

Supplier: Vivacity Engineering Pty Ltd
ABN: 78 305 545 664
Street Address: 3 Sefton Road
Thornleigh
NSW 2120
Australia
Telephone: +61 2 9875 3044
Facsimile: +61 2 9875 3665
Email: info@megapoxy.com

Emergency Telephone number: +61 2 9875 3044

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Danger

Hazard Classifications

Acute Toxicity - Oral - Category 3
Acute Toxicity - Dermal - Category 3
Skin Corrosion/Irritation - Category 1B
Serious Eye Damage/Irritation - Category 2A
Sensitisation - Skin - Category 1
Chronic Hazard to the Aquatic Environment - Category 2

Hazard Statements

H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Prevention Precautionary Statements

P261 Avoid breathing dust, fume, gas, mist, vapours or spray..
P264 Wash hands, face and all exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

Response Precautionary Statements

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

Safety Data Sheet

Megapoxy

skin with water/shower.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/physician.

Storage Precautionary Statement

Not allocated

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: S5. Caution

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 9

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;

- (a) packagings that do not incorporate a receptacle exceeding 500 Kg (L); or
- (b) IBCs.

3. COMPOSITION INFORMATION

| CHEMICAL ENTITY | CAS NO | PROPORTION |
|--|------------|------------|
| Bisphenol-A epoxy resin | 25068-38-6 | 30-60 % |
| Cresylic acid | 1319-77-3 | 1-9 % |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives | 68609-97-2 | 1-9 % |
| Ingredients determined to be Non-Hazardous | | Balance |
| | | <hr/> 100% |

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: Effects may be delayed. This material, or a component of the material, can be absorbed through the skin with resultant toxic effects. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open.

Safety Data Sheet

Megapoxy

Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor. Transport to a doctor or hospital quickly.

PPE for First Aiders: Wear safety shoes, gloves, safety glasses. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3Z

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: Not applicable.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 47

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 9 Miscellaneous Dangerous Good as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison Schedule 5 (Caution) and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

| | TWA | | STEL | | NOTICES |
|---------------------|-----|-------|------|-------|---------|
| | ppm | mg/m3 | ppm | mg/m3 | |
| Cresol, all isomers | 5 | 22 | - | - | Sk |

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

Personal Protection Equipment: SAFETY SHOES, GLOVES, SAFETY GLASSES.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, gloves, safety glasses. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Colour: Viscous white/natural
Odour: Phenolic

Solubility: Insoluble in water

Safety Data Sheet

Megapoxy

| | |
|----------------------------------|----------------------|
| Specific Gravity (20 °C): | 1.68-1.72 @ 25 Deg C |
| Relative Vapour Density (air=1): | 8 |
| Vapour Pressure (20 °C): | <0.01 Pa |
| Flash Point (°C): | >200 Deg C |
| Boiling Point/Range (°C): | >200 Deg C |
| Decomposition Point (°C): | >200 Deg C |
| Total VOC (g/Litre): | Nil |
| % Volatile by Volume: | Nil |

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Toxic in contact with skin. Can be absorbed through the skin with resultant toxic effects. Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Toxic if swallowed. Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Acute toxicity

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 20.0 mg/L for vapours or LC50 > 5.0 mg/L for dust and mist or LC50 > 20,000 ppm for gas

Skin contact: This material has been classified as a Category 3 Hazard. Acute toxicity estimate (based on ingredients): 200 - 1,000 mg/Kg bw

Ingestion: This material has been classified as a Category 3 Hazard. Acute toxicity estimate (based on ingredients): 50 - 300 mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as a Category 1B Hazard (irreversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has

Safety Data Sheet

Megapoxy

been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as a Category Chronic 2 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 1 - 10 mg/L, where the substance is not rapidly degradable and/or BCF \geq 500 and/or log $K_{ow} \geq$ 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;

- (a) packagings that do not incorporate a receptacle exceeding 500 Kg (L); or
- (b) IBCs.

Safety Data Sheet

Megapoxy



| | |
|---|--|
| UN No: | 3082 |
| Dangerous Goods Class: | 9 |
| Subsidiary Risk, Secondary Subsidiary: | |
| Packing Group: | III |
| Special Provisions: | 179, 274, 331 |
| Limited Quantities: | 5 L |
| Hazchem Code: | •3Z |
| Emergency Response Guide No: | 47 |
| Packagings and IBCs | |
| Packing Instructions | P001, LP01 |
| Special Packing Provisions | |
| Portable Tanks and Bulk Containers | |
| Instructions | T4 |
| Special Provisions | TP1, TP29 |
| Proper Shipping Name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin) |

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1). Note 1: Materials that are fire risks are incompatible with oxidising agents (Class 5.1) or organic peroxides (Class 5.2). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



| | |
|---|---|
| UN No: | 3082 |
| Dangerous Goods Class: | 9 |
| Subsidiary Risk, Secondary Subsidiary: | |
| Packing Group: | III |
| Special Provisions: | 179, 274, 331 |
| Limited Quantities: | 5 L |
| Hazchem Code: | •3Z |
| Emergency Response Guide No: | 47 |
| EMS fire: | F-A |
| EMS spill: | S-F |
| Packagings and IBCs | |
| Packing Instructions: | P001, LP01 |
| Special Packing Provisions: | |
| Portable Tanks and Bulk Containers | |
| Instructions: | |
| Special Provisions: | TP1, TP29 |
| Proper Shipping Name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin) |

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous

Safety Data Sheet

Megapoxy

Goods Regulations for transport by air.



| | |
|---|--|
| UN No: | 3082 |
| Dangerous Goods Class: | 9 |
| Subsidiary Risk, Secondary Subsidiary: | |
| Packing Group: | III |
| Special Provisions: | A97 A158 |
| ERG Code: | 9L |
| Passengers and Cargo Aircraft Limited Quantities | |
| Packing Instructions: | Y914 |
| Maximum Net Quantity per Package: | 30 kg G |
| Passengers and Cargo Aircraft | |
| Packing Instructions: | 914 |
| Maximum Net Quantity per Package: | 450 L |
| Cargo Aircraft Only | |
| Packing Instructions: | 914 |
| Maximum Net Quantity per Package: | 450 L |
| Proper Shipping Name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin) |

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives

This material/constituent(s) is covered by the following requirements:

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Reason for issue: Change to Transport Information

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards

Safety Data Sheet

Megapoxy

described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.