

108

Part B

Liquid Epoxy Resin

Safety Data Sheet

Hazardous Chemical, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION	
PRODUCT NAME	Megapoxy 108 - Part B
RECOMMENDED USE	Liquid epoxy for civil engineering applications where early development of high strength is essential.
SUPPLIER	Vivacity Engineering Pty Ltd.
ABN	78 305 545 664
STREET ADDRESS	3 Sefton Road Thornleigh NSW 2120 Australia
TELEPHONE	+61 2 9875 3044
EMAIL	info@megapoxy.com
EMERGENCY TELEPHONE NUMBER	+61 2 9875 3044 Australia: 13 11 26 (Poisons Information Centre) New Zealand: 0800 764 766 (NZ Poisons & Hazardous Chemicals Centre)

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia GHS 7.





SIGNAL WORD	Danger
HAZARD CLASSIFICATIONS	Acute Toxicity - Oral - Category 4 Skin Corrosion/Irritation - Category 1B
	Serious Eye Damage/Irritation - Category 1
	Sensitisation - Skin - Category 1
	Chronic Hazard to the Aquatic Environment - Category 3

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com





HAZARD STATEMENTS	H302	Harmful if swallowed.
	H312	Harmful in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H317	May cause an allergic skin reaction.
	H412	Harmful to aquatic life with long lasting effects.
PREVENTION PRECAUTIONARY	P261	Avoid breathing dust, fume, gas, mist, vapours or spray.
STATEMENTS	P264	Wash hands, face and all exposed skin thoroughly after handling.
	P270	Do not eat, drink or smoke when using this product.
	P273	Avoid release to the environment.
RESPONSE PRECAUTIONARY STATEMENTS	P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER or doctor/physician.
STORAGE PRECAUTIONARY STATEMENT	P405	Store locked up.
DISPOSAL PRECAUTIONARY STATEMENT	P501	Dispose of contents/container in accordance with local, regional, national and international regulations.
POISON SCHEDULE	S5. Caution	
DANGEROUS GOOD CLASSIFICATION	Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".	
DANGEROUS GOODS CLASS	8	

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION	
1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-	112-24-3	30-60 %	
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-	2855-13-2	30-60 %	
Ingredients determined to be Non-Hazardous		Balance	
		100%	

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com







Safety Data Sheet

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

INHALATION	Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.
SKIN CONTACT	Effects may be delayed. This material, or a component of the material, can be absorbed through the skin with resultant toxic effects. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.
EYE CONTACT	Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.
INGESTION	Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.
PPE FOR FIRST AIDERS	Wear safety shoes, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.
NOTES TO PHYSICIAN	Treat symptomatically. Effects may be delayed. Can cause corneal burns.

5. FIRE FIGHTING MEASURES	
HAZCHEM CODE	2X
SUITABLE EXTINGUISHING MEDIA	If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).
SPECIFIC HAZARDS	Non-combustible material.
FIRE FIGHTING FURTHER ADVICE	Not applicable.

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com







6. ACCIDENTAL RELEASE MEASURES	
SMALL SPILLS	Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.
LARGE SPILLS	Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.
DANGEROUS GOODS - INITIAL EMERGENCY RESPONSE GUIDE NO:	36

7. HANDLING AND STORAGE	
HANDLING	Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.
STORAGE	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.
	This material is classified as a Class 8 Corrosive as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations. This material is a Scheduled Poison Schedule 5 (Caution) and must be stored, maintained and used in
	accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION	
NATIONAL OCCUPATIONAL EXPOSURE LIMITS	No value assigned for this specific material by Safe Work Australia.
BIOLOGICAL LIMIT VALUES	As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.
ENGINEERING MEASURES	Natural ventilation should be adequate under normal use conditions.
PERSONAL PROTECTION EQUIPMENT	SAFETY SHOES, GLOVES, SAFETY GLASSES. Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Wear safety shoes, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com





HYGIENE MEASURES

Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Clear Liquid
Colour:	Clear to Pale
Odour:	Amine
Solubility:	Miscible in water and other solvents
Specific Gravity (20 °C):	0.96-0.98 @ 25 Deg C
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	<0.01 Pa
Flash Point (°C):	148
Flammability Limits (%):	lower: 1.2
Boiling Point/Range (°C):	247 Deg C
Decomposition Point (°C):	>293 Deg C
pH:	11.6
Total VOC (g/Litre):	Nil
% Volatile by Volume:	Nil

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable.

10. STABILITY AND REACTIVITY	
CHEMICAL STABILITY	This material is thermally stable when stored and used as directed.
CONDITIONS TO AVOID	Elevated temperatures and sources of ignition.
INCOMPATIBLE MATERIALS	Oxidising agents.
HAZARDOUS DECOMPOSITION PRODUCTS	Oxides of carbon and nitrogen, smoke and other toxic fumes.
HAZARDOUS REACTIONS	No known hazardous reactions.

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com





Safety Data Sheet

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

ACUTE EFFECTS

Material may be an irritant to mucous membranes and respiratory tract.

Skin contact

Harmful in contact with skin. Can be absorbed through the skin with resultant toxic effects. Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion

Harmful if swallowed. Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

Eye contact

A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

ACUTE TOXICITY

Inhalation

This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): $LC_{50} > 20.0$ mg/L for vapours or $LC_{50} > 5.0$ mg/L for dust and mist or $LC_{50} > 20,000$ ppm for gas.

This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw.

Ingestion

This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients): 300 - 2,000 mg/Kg bw.

Corrosion/Irritancy

Eye: this material has been classified as a Category 1 Hazard (irreversible effects to eyes). Skin: this material has been classified as a Category 1B Hazard (irreversible effects to skin).

Sensitisation

Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard

This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure)

This material has been classified as non-hazardous.

CHRONIC TOXICITY

Mutagenicity

This material has been classified as non-hazardous.

Carcinogenicity

This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation)

This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure)

This material has been classified as non-hazardous.

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com





Safety Data Sheet

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

ACUTE AQUATIC HAZARD	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L.
LONG-TERM AQUATIC HAZARD	This material has been classified as a Category Chronic 3 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): $10 - 100 \text{ mg/L}$, where the substance is not rapidly degradable and/or BCF $\geq 500 \text{ and/or log K}_{ow} \geq 4$.
ECOTOXICITY	No information available.
PERSISTENCE AND DEGRADABILITY	No information available.
BIOACCUMULATIVE POTENTIAL	No information available.
MOBILITY	No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com





14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No:	2289
Dangerous Goods Class:	8
Subsidiary Risk, Secondary Subsidiary:	
Packing Group:	III
Special Provisions:	
Limited Quantities:	5 L
Hazchem Code:	2X
Emergency Response Guide No:	36
Packagings and IBCs	
Packing Instructions	P001, IBC03, LP01
Special Packing Provisions	
Portable Tanks and Bulk Containers	
Instructions	T4
Special Provisions	TP1
Proper Shipping Name:	ISOPHORONEDIAMINE
Segregation Dangerous Goods:	Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), radioactive substances (Class 7) or food and food packaging in any quantity. Note 1: Concentrated strong alkalis are incompatible with concentrated strong acids. Note 2: Concentrated strong acids are incompatible with concentrated strong alkalis. Note 3: Acids are incompatible with Dangerous Goods of Class 6 which are cyanides. Exemptions may apply.

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com







MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.



UN No:	2289
Dangerous Goods Class:	8
Subsidiary Risk, Secondary Subsidiary:	
Packing Group:	III
Special Provisions:	
Limited Quantities:	5 L
Hazchem Code:	2X
Emergency Response Guide No:	36
EMS fire:	F-A
EMS spill:	S-B
Packagings and IBCs	
Packing Instructions:	P001, IBC03, LP01
Special Packing Provisions:	
Portable Tanks and Bulk Containers	
Instructions:	T4
Special Provisions:	TP1
Proper Shipping Name:	ISOPHORONEDIAMINE

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com





Safety Data Sheet

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No:	2289
Dangerous Goods Class:	8
Subsidiary Risk, Secondary Subsidiary:	
Packing Group:	III
Special Provisions:	A803
ERG Code:	8L
Passengers and Cargo Aircraft Limited Quantities	
Packing Instructions:	Y841
Maximum Net Quantity per Package:	1L
Passengers and Cargo Aircraft	
Packing Instructions:	852
Maximum Net Quantity per Package:	5 L
Cargo Aircraft Only	
Packing Instructions:	856
Maximum Net Quantity per Package:	60 L
Proper Shipping Name:	ISOPHORONEDIAMINE

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

· Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives

This material/constituent(s) is covered by the following requirements:

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com



Safety Data Sheet

16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com

