Megapoxy

Methylated Spirits

Cleaner Solvent

Safety Data Sheet

Hazardous Chemical, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION		
PRODUCT NAME	Megapoxy Methylated Spirits	
RECOMMENDED USE	Thinners for epoxy products, cleaning and degreasing surfaces.	
SUPPLIER	Vivacity Engineering Pty Ltd.	
ABN	78 305 545 664	
STREET ADDRESS	3 Sefton Road Thornleigh NSW 2120 Australia	
TELEPHONE	+61 2 9875 3044	
EMAIL	info@megapoxy.com	
EMERGENCY TELEPHONE NUMBER	+61 2 9875 3044 Australia: 13 11 26 (Poisons Information Centre) New Zealand: 0800 764 766 (NZ Poisons & Hazardous Chemicals Centre)	

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia GHS 7.



SIGNAL WORD	Danger	
HAZARD CLASSIFICATIONS	Flammable Liquids - Category 2 Serious Eye Damage/Irritation - Category 2A	
HAZARD STATEMENTS	H225	Highly flammable liquid and vapour.
	H319	Causes serious eye irritation.

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com VIVACITY ENGINEERING PTY LTD ABN: 78 305 545 664

Megapoxy

Safety Data Sheet

PREVENTION	P210	Keep away from all sources of ignition. No smoking.	
PRECAUTIONARY STATEMENTS	P233	Keep container tightly closed.	
STATEMENTS	P240	Ground/bond container and receiving equipment.	
	P241	Use explosion-proof electrical, ventilating, lighting and all other equipment.	
	P242	Use only non-sparking tools.	
	P243	Take precautionary measures against static discharge.	
	P264	Wash hands, face and all exposed skin thoroughly after handling.	
	P280	Wear protective clothing, gloves, eye/face protection and suitable respirator.	
RESPONSE PRECAUTIONARY	P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
STATEMENTS	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
	P337+P313	If eye irritation persists: Get medical advice/attention.	
	P370+P378	In case of fire: Use alcohol resistant foam, fine water spray or water fog for extinction.	
STORAGE PRECAUTIONARY STATEMENT	P403+P235	Store in a well-ventilated place. Keep cool.	
DISPOSAL PRECAUTIONARY STATEMENT	P501	Dispose of contents/container in accordance with local, regional, national and international regulations.	
POISON SCHEDULE	S5. Caution		
DANGEROUS GOOD CLASSIFICATION		rous Goods by the criteria of the "Australian Code for the Transport of Dangerous ill" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".	
DANGEROUS GOODS CLASS	3		

3. COMPOSITION INFORMATION					
CHEMICAL ENTITY	CAS NO	PROPORTION			
Ethanol	64-17-5	>60 %			
Ingredients determined to be Non-Hazardous		Balance			
		100%			

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com VIVACITY ENGINEERING PTY LTD ABN: 78 305 545 664

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

INHALATION	Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.
SKIN CONTACT	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness blistering, or irritation occurs seek medical assistance.
EYE CONTACT	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.
INGESTION	Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.
PPE FOR FIRST AIDERS	Wear safety shoes, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.
NOTES TO PHYSICIAN	Treat symptomatically.

5. FIRE FIGHTING MEASURES		
HAZCHEM CODE	•2YE	
SUITABLE EXTINGUISHING MEDIA	lf material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, dry agent (carbon dioxide, dry chemical powder).	
SPECIFIC HAZARDS	Highly flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.	
FIRE FIGHTING FURTHER ADVICE	Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.	

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com

VIVACITY ENGINEERING PTY LTD ABN: 78 305 545 664



6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS	Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.
LARGE SPILLS	If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.
DANGEROUS GOODS - INITIAL EMERGENCY RESPONSE GUIDE NO:	14

7. HANDLING AND STORAGE		
HANDLING	Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols.	
STORAGE	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.	
	This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations. This material is a Scheduled Poison Schedule 5 (Caution) and must be stored, maintained and used in accordance with the relevant regulations.	

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com VIVACITY ENGINEERING PTY LTD ABN: 78 305 545 664

World-leading epoxy adhesive solutions

Megapoxy



Megapoxy


Safety Data Sheet

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

NATIONAL OCCUPATIONAL EXPOSURE LIMITS		T ppm	⁻WA mg/m³	s ppm	STEL mg/m ³	NOTICES
EXPOSORE LIMITS	Ethyl alcohol	1000	1880	-	-	-
	As published by Safe Work Australia.					
	TWA - The time-weighted average airborne concent day working week over an entire working life.	tration ove	er an eighl	-hour w	vorking day	, for a five-
	STEL (Short Term Exposure Limit) - the average air which should not be exceeded at any time during a					period
	These Exposure Standards are guides to be used in All atmospheric contamination should be kept too a standards should not be used as fine dividing lines chemicals. They are not a measure of relative toxici	as low a le [.] between s	vel as is wo	orkable.	These exp	osure
	If the directions for use on the product label are follo should not exceed the above standard. The standar potentially exposed during product manufacture.					
BIOLOGICAL LIMIT VALUES	As per the "National Model Regulations for the Con Work Australia)" the ingredients in this material do i					es (Safe
ENGINEERING MEASURES	Ensure ventilation is adequate to maintain air conce in well ventilated areas. Use with local exhaust vent Vapour heavier than air - prevent concentration in h where vapour may have collected.	ilation or v	, while wear	ing app	ropriate res	spirator.
PERSONAL	SAFETY SHOES, GLOVES, SAFETY GLASSES, RESP	IRATOR.				
PROTECTION EQUIPMENT	Personal protective equipment (PPE) must be suita associated with the work as identified by the risk as				rk and any	hazard
	Wear safety shoes, gloves, safety glasses, respirator exists wear organic vapour/particulate respirator m NZS 1716. Available information suggests that glove intermittent contact. However, due to variations in o should make a final assessment. Always wash hand toilet. Wash contaminated clothing and other protect	neeting the s made fro glove cons s before si	e requiren om nitrile i struction a moking, ea	nents of rubber s nd local ating, dr	AS/NZS 17 should be s conditions inking or u	'15 and AS/ uitable for s, the user sing the
HYGIENE MEASURES	Keep away from food, drink and animal feeding stuf hands prior to eating, drinking or smoking. Avoid co repeated or prolonged skin contact. Avoid inhalation stations and safety showers are close to the worksta	ntact with n of vapou	n clothing. ur, mist or a	Avoid e	ye contact	and

 3 Sefton Road, Thornleigh NSW 2120 Australia
 P: +61 (02) 9875 3044
 E: info@megapoxy.com
 megapoxy.com

 VIVACITY ENGINEERING PTY LTD
 ABN: 78 305 545 664



Megapoxy[®]

Safety Data Sheet

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Clear Liquid
Colour:	Clear
Solubility:	Completely soluble
Specific Gravity (20 °C):	0.79-0.8 @ 25 Deg C
Vapour Pressure (20 °C):	5.9 kPa @ 20 deg C
Flash Point (°C):	13-18 Deg C
Boiling Point/Range (°C):	78 Deg C
Total VOC (g/Litre):	No Data Available
% Volatile by Volume:	No Data Available

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable.

10. STABILITY AND REACTIVITY	
CHEMICAL STABILITY	This material is thermally stable when stored and used as directed.
CONDITIONS TO AVOID	Elevated temperatures and sources of ignition.
INCOMPATIBLE MATERIALS	Oxidising agents.
HAZARDOUS DECOMPOSITION PRODUCTS	Oxides of carbon and nitrogen, smoke and other toxic fumes.
HAZARDOUS REACTIONS	No known hazardous reactions.

 3 Sefton Road, Thornleigh NSW 2120 Australia
 P: +61 (02) 9875 3044
 E: info@megapoxy.com
 megapoxy.com

 VIVACITY ENGINEERING PTY LTD
 ABN: 78 305 545 664



Safety Data Sheet

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

ACUTE EFFECTS	Inhalation
	Material may be an irritant to mucous membranes and respiratory tract.
	Skin contact
	Contact with skin may result in irritation.
	Ingestion
	Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.
	Eye contact
	An eye irritant.
ACUTE TOXICITY	Inhalation
	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): $LC_{50} > 20.0 \text{ mg/L}$ for vapours or $LC_{50} > 5.0 \text{ mg/L}$ for dust and mist or $LC_{50} > 20,000 \text{ ppm}$ for gas. Skin contact
	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw.
	Ingestion
	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw.
	Corrosion/Irritancy
	Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as not corrosive or irritating to skin.
	Sensitisation
	Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.
	Aspiration hazard
	This material has been classified as non-hazardous.
	Specific target organ toxicity (single exposure)
	This material has been classified as non-hazardous.
CHRONIC TOXICITY	Mutagenicity
	This material has been classified as non-hazardous.
	Carcinogenicity
	This material has been classified as non-hazardous.
	Reproductive toxicity (including via lactation)
	This material has been classified as non-hazardous.
	Specific target organ toxicity (repeat exposure)
	This material has been classified as non-hazardous.

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com VIVACITY ENGINEERING PTY LTD ABN: 78 305 545 664

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

ACUTE AQUATIC HAZARD	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L.	
LONG-TERM AQUATIC HAZARD	This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K _{ow} < 4.	
ΕCOTOXICITY	No information available.	
PERSISTENCE AND DEGRADABILITY	No information available.	
BIOACCUMULATIVE POTENTIAL	No information available.	
MOBILITY	No information available.	

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

3 Sefton Road, Thornleigh NSW 2120 Australia | P: +61 (02) 9875 3044 | E: info@megapoxy.com | megapoxy.com VIVACITY ENGINEERING PTY LTD | ABN: 78 305 545 664



14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Megapoxy



UN No:	1170
Dangerous Goods Class:	3
Subsidiary Risk, Secondary Subsidiary:	
Packing Group:	II
Special Provisions:	144
Limited Quantities:	1L
Hazchem Code:	•2YE
Emergency Response Guide No:	14
Packagings and IBCs	
Packing Instructions	P001, IBC02
Special Packing Provisions	
Portable Tanks and Bulk Containers	
Instructions	T4
Special Provisions	TP1
Proper Shipping Name:	ETHANOL
Segregation Dangerous Goods:	Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com VIVACITY ENGINEERING PTY LTD ABN: 78 305 545 664



MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.



UN No:	1170
Dangerous Goods Class:	3
Subsidiary Risk, Secondary Subsidiary:	
Packing Group:	II
Special Provisions:	144
Limited Quantities:	1 L
Hazchem Code:	•2YE
Emergency Response Guide No:	14
EMS fire:	F-E
EMS spill:	S-D
Packagings and IBCs	
Packing Instructions:	P001, IBC02
Special Packing Provisions:	
Portable Tanks and Bulk Containers	
Instructions:	T4
Special Provisions:	TP1
Proper Shipping Name:	ETHANOL

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com VIVACITY ENGINEERING PTY LTD ABN: 78 305 545 664



Safety Data Sheet

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No:	1170	
Dangerous Goods Class:	3	
Subsidiary Risk, Secondary Subsidiary:		
Packing Group:	II	
Special Provisions:	A3, A58, A180	
ERG Code:	3L	
Passengers and Cargo Aircraft Limited Quantities		
Packing Instructions:	Y341	
Maximum Net Quantity per Package:	1L	
Passengers and Cargo Aircraft		
Packing Instructions:	353	
Maximum Net Quantity per Package:	5 L	
Cargo Aircraft Only		
Packing Instructions:	364	
Maximum Net Quantity per Package:	60 L	
Proper Shipping Name:	ETHANOL	

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

Organic solvents excluding halogenated solvents

This material/constituent(s) is covered by the following requirements:

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

 3 Sefton Road, Thornleigh NSW 2120 Australia
 P: +61 (02) 9875 3044
 E: info@megapoxy.com
 megapoxy.com

 VIVACITY ENGINEERING PTY LTD
 ABN: 78 305 545 664



Safety Data Sheet

16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

3 Sefton Road, Thornleigh NSW 2120 Australia P: +61 (02) 9875 3044 E: info@megapoxy.com megapoxy.com VIVACITY ENGINEERING PTY LTD ABN: 78 305 545 664